CUSTOMER: 572435 BATCH#: 1917445 PICK ZONE: CSE2 PRODUCT NAME: PREMALUBE ORDER #: 2962554 DELIVERY ID: 14509292 PICK SEQUENCE #: 680 **BARCODE #: 10032735**

Safety Data Sheet PREMALUBE

Supercedes Date 04/18/2014

Issuing Date 12/21/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name PREMALUBE Recommended use Lubricant Information on Manufacturer CERTIFIED LABS, DIV. OF NCH CORP.

BOX 152170 IRVING, TEXAS 75015 Product Code 10032735 Chemical nature Petroleum oil blend **Emergency Telephone Number** CHEMTREC® 800-424-9300 Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Odor Oily Coior Black Physical state Grease

GHS

Classification Physical Hazards

Health Hazard None

Other hazards

None

Labeling Signal Word Not classified

10 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5	60-100
Aluminum benzoate fatty acid complex	82980-54-9	7-13
Calcium carbonate	471-34-1	7-13
Molybdenum disulfide	1317-33-5	0.1-1
Barium dinonylnaphthalene sulfonate	25619-56-1	0.1-1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice

Avoid contact with skin, eyes and clothing.

Eye Contact

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation

develops and persists. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and

Skin Contact

persists.

inhaiation ingestion

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Notes to physician

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.

Treat symptomatically.

5. FIRE-FIGHTIN 3 MEASURES

Flash Point 450 °F / 232 °C

Method Open cup

Flammability Limits in Air %: No information available.

Upper: No dala available

Lower: No data available

Sultable Extinguishing Media

Water spray, Foam, Carbon dioxide (CO2), Dry chemical, Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

Specific hazards arising from the chemical

Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure -demand, NOHSC (approved or equivalent) and full protective gear.

NFPA

Heaith 1

Fiammability 1

instability 0

HMIS

Heaith 1

Fiammablilty 1

instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment. Prevent further leakage or spillage if safe to do so. Material can

create slippery conditions.

Environmental Precautions Methods for Containment

Do not flush into surface water or sanitary sewer system.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up

Pick up and transfer to properly labeled containers.

Neutralizing Agent

Not applicable.

7. HANDLING AND STORAGE

Handiing

Avoid contact with skin, eyes and clothing.

Storage

Store in original container. Keep containers tightly closed in a dry, cool and well -ventilated place.

Storage Temperature

Minimum

10 °F / -12 °C

Maximum

150 °F / 66 °C

Storage Conditions

Indoor

Outdoor

X

Heated

Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	TWA: 5 mg/m ³ ; STEL: 10 mg/m ³	TWA: 5 mg/m ³	No data available
Calcium carbonate	No data available	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
		TWA: 5 mg/m ³ respirable fraction	I VVA: 5 mg/m² respirable dusi
Molybdenum disulfide	TWA: 10 mg/m ³ inhalable fraction	TWA: 15 mg/m ³ total dust	No data available
	TWA: 3 mg/m ³ respirable fraction		
Barium dinonylnaphthalene sulfonate	TVVA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should

be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

General Hygiene Considerations

Fiammability Limits in Air %:

Eve/Face Protection Skin Protection

Safety glasses with side-snields.

For prolonged or repeated contact, use protective gloves with appropriate chemical resistance. In case of inadequate ventilation wear respiratory protection. When workers are facing

Respiratory Protection concentrations above the exposure limit they must use appropriate certified respirators.

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Grease Color Black **Odor Threshold** Not applicable Not applicable рΗ **Evaporation Rate** 0 (BuAc = 1)

VOC Content (%) Vapor Pressure <0.01 mmHg @ 70°F Solubility Negligible

Meiting Point/Range No data available **Boiling Point/Range** No data available Fiash Point 450 °F / 232 °C Autoignition Temperature

No information available. No information available

Semi-Solid Viscosity Odor Oily Appearance Opaque 0.92 Specific Gravity Percent Voiatile (Voiume) VOC Content (g/L)

Vapor Density 11.3 (Air = 1.0)No data available n-Octanoi/Water Partition **Decomposition Temperature** No data available No data available Flammability (solid, gas) Method Open cup

Upper: No data available Lower: No data available

10. STABILITY AND REACTIVITY

Chemical Stability
Conditions to Avoid

Incompatible Products
Decomposition Temperature
Hazardous Decomposition Products

Possibility of Hazardous Reactions

Stable. Hazardous polymerization does not occur.

Extremes of temperature and direct sunlight, Keep away from open

fiames, hot surfaces, and sources of ignition.

Strong oxidizing agents, Acids, Bases.

No data available

Carbon oxides, Sulfur oxides, Oxides of

phosphorus, Hydrocarbons, Aldehydes, Ketones.

None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information

No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Orai LD50 Dermai LD50 No information available

inhaiation LC50

No information available

Gas Mist Vapor No information available No information available No information available

Principle Route of Exposure

Eye contact, Skin contact.

Primary Routes of Entry

Eye contact.

Acute Effects:

Inhalation

Eyes Skin

Low hazard for usual industrial or commercial handling. Low hazard for usual industrial or commercial handling. Low hazard for usual industrial or commercial handling.

ingestion
Chronic Toxicity

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged skin contact may defat the skin and produce dermatitis.

Target Organ Effects

Respiratory system, Eyes, Skin.

Aggravated Medicai Conditions

Respiratory disorders, Skin disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermai LD50	inhalation LC50	Draize Test	Other
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	No data available	No data available	No data available
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	no data available	No data available	No data available	No data available
Molybdenum disulfide 1317-33-5	No data available	no data available	> 2820 mg/m ³ (Rat) 4 h	No data available	No data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Calcium carbonate	No data available	No data available	No data available	No data available	Skin; Eyes; Respiratory system
471-34-1					

Carcinogenicity

There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	Partition	l
					coefficien	1
Petroleum distillates, hydrotreated	No information available.	LC50 > 5000 mg/L Oncorhynchus	No information available	1000: 48 h Daphnia	N/A	l
heavy naphthenic (<3% DMSO		mykiss 96 h		magna mg/L EC50		l
extractable)						ı

Persistence and Degradability

No information available.

Bioaccumulation

No information available. No information available.

Mobility

13. DISPOSAL CONSIDERATIONS

Product Disposal Container Disposal Dispose of in accordance with local regulations.

Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT

Not regulated

TDG

Not regulated

ICAO

Not regulated

IATA

Not regulated

IMDG/IMO

Not regulated

15. REGULATORY INFORMATION

Inventories

TSCA DSL Complies

Complies

U.S. Federai Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals

which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Component	CAS No.	Weight %	SARA 313 - Threshold Values
Barium dinonylnaphthalene sulfonate	25619-56-1	0.1-1	1.0
SARA 311/312 Hazardous Categorization			

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
No	No	No	No	No

CERCLA

16. OTHER INFORMATION

Prepared By

Adrienne McKee

Supercedes Date

04/18/2014 12/21/2016

issuing Date

No information available.

Reason for Revision

No information available.

Giossary

No information available.

List of References.

No information available

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.